AMENDMENTS TO THE CLAIMS

Listing of the Claims:

The listing of claims will replace all prior versions, and listings, of claims in the application:

 (Currently Amended) <u>A method Method</u> of painting a substrate with an emulsion paint comprising spherical polymer particles, characterized in that comprising the steps of:

applying a first coating in a first opaque layer; and

<u>applying</u> the emulsion paint is <u>applied</u> in a <u>second</u> semi-opaque-layer over <u>the first</u> [[an]] opaque layer, of a first coating, and in that

wherein the spherical polymer particles in the emulsion paint show a particle size distribution in which 3-10% of the particles have an average particle size between 63-90 micrometers and 25-40% have a particle size between 40-63 micrometers.

- (Currently Amended) The method Method according to claim 1, characterized in that
 wherein the opaque layer is a first color and the semi-opaque layer is a second color, and the first
 color and the second color are the same layers are of a corresponding colour.
- (Currently Amended) The method Method according to claim 1, characterized in that wherein the opaque layer is made of an aqueous pigmented primer comprising an acrylic binder.
- (Currently Amended) The method Method according to claim 1-characterized in that the top coat wherein the second semi-opaque layer is applied by brush in cross-way fashion.
- (Currently Amended) <u>The method Method</u> according to claim 1, characterized in that the top coat wherein the second semi-opaque layer is applied by a roller and, further comprising;

that subsequently a tool is used comprising dragging a flat side of a tool provided with fibrous material, preferably of stiff parallel projecting fibres such as synthetic grass fibres, and in that the fibrous flat side is dragged over the freshly applied second semi-opaque layer top-coat.

6. (Currently Amended) A substrate Substrate provided with a multi-layer effect coating

applied by the [[a]] method according to claim 1.

- (Currently Amended) <u>An emulsion Emulsion paint composition comprising:</u>
 spherical polymer particles, eharacterized in that wherein 3-10% of the spherical particles have a particle size between 63-90 micrometers and 25-40% of the spherical particles have a particle size between 40-63 micrometers.
- (Currently Amended) The paint Paint composition according to claim 7, eharacterized in that wherein at least a portion of the spherical particles are polyurethane particles.
- (Currently Amended) The paint Paint composition according to claim 7, eharacterized in
 that the specific density of wherein the particles have a specific density [[is]] between 0.8-1.5
 g/cm³ g/cm³.
- (Currently Amended) <u>The paint Paint</u> composition according to claim 7, characterized in that wherein the spherical particles are pre-pigmented.
- (Currently Amended) <u>The paint Paint</u> composition according to claim 7, eharacterized in that wherein the paint comprises wood <u>fibers</u> fibres with a length between 25-35 microns.
- 12. (Currently Amended) <u>A set Set of paint products comprising:</u> a semi-opaque emulsion paint according to claim 7 of a first color; and an opaque aqueous acrylic coating composition of a <u>second color</u>, wherein the first color and the second color are the <u>same</u> corresponding colour.
- (Currently Amended) <u>The set Set of paint products according to claim 12, further comprising: characterized in that the set includes a tool with a flat side provided with a fibrous material.</u>
- 14. (New) The method according to claim 5, wherein the fibrous material comprises stiff parallel projecting fibers.

15. (New) The method according to claim 5, wherein the fibrous material comprises synthetic grass fibers.